

BATTERY-BOX PREMIUM HVL (US)




- Capable of High-Powered Emergency-Backup and Off-Grid Functionality
- Highest Efficiency Thanks to a Real High-Voltage Series Connection
- The Patented Modular Plug Design Requires no Internal Wiring and Allows for Maximum Flexibility and Ease of Use
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: Maximum Safety, Life Cycle, and Power
- Compatible with Leading High Voltage Battery Inverters
- Highest Safety Standards

BATTERY-BOX PREMIUM HVL

One Battery-Box Premium HVL is composed of 3 to 8 HVL battery modules that are connected in series to achieve a usable capacity of 12 to 32 kWh.

Ability to scale by adding HVL modules later.




FLEXIBLE, EFFICIENT, SIMPLE



Internal Plug Connection
No Additional Wiring Required



12 - 32 kWh
Tailored Sizing for Each Application









Extend Anytime
Easily Adapts to New Requirements



High Power
Power for Every Application

TECHNICAL PARAMETERS PREMIUM HVL

						
	HVL 12.0	HVL 16.0	HVL 20.0	HVL 24.0	HVL 28.0	HVL 32.0
Battery Module	HVL (4 kWh, 51.2 V, 99.2 lb)					
Number of Modules	3	4	5	6	7	8
Usable Energy [1]	12 kWh	16 kWh	20 kWh	24 kWh	28 kWh	32 kWh
Max Output Current [2]	50 A	50 A	50 A	50 A	50 A	50 A
Peak Output Current [2]	75 A, 3 s	75 A, 3 s	75 A, 3 s	75 A, 3 s	75 A, 3 s	75 A, 3 s
Nominal Voltage	153.6 V	204.8 V	256 V	307.2 V	358.4 V	409.6 V
Operating Voltage	120~173 V	160~230 V	200~288 V	240~345 V	280~403 V	320~460 V
Dimensions (H/W/D)	39.2 x 23.0 x 11.7 inch	48.3 x 23.0 x 11.7 inch	57.5 x 23.0 x 11.7 inch	66.7 x 23.0 x 11.7 inch	75.9 x 23.0 x 11.7 inch	85.0 x 23.0 x 11.7 inch
Weight	330.7 lb	429.9 lb	529.1 lb	628.3 lb	727.5 lb	826.7 lb
Operating Temperature	14 °F to 122 °F					
Battery Cell Technology	Lithium Iron Phosphate (cobalt-free)					
Communication	CAN/RS485					
Enclosure Protection Rating	NEMA 3R					
Round-trip Efficiency	≥96%					
Certification	UL1973 / IEC60730 / FCC / UN38.3					
Applications	ON Grid / ON Grid + Backup / OFF Grid					
Warranty [3]	10 Years					
Compatible Inverters	Refer to BYD Battery-Box Premium HVL Compatible Inverter List					

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at 77 °F. System usable energy may vary due to system configuration parameters.

[2] Charge derating will occur between 14 °F and 41 °F

[3] Conditions apply. Refer to BYD Battery-Box Premium Limited Warranty Letter.

